

## **Technical data sheet**

## **KEMOTON PLUS**

## Pigment preparation



product description: KEMOTON PLUS pigment preparation is a water preparation based on quality pigments.

area of application: Intended for tinting of all types of interior wall paint and water-based topcoats: Aqualux

topcoat and Aqualux Strong.

Pigment preparation is produced in 11 shades: yellow, ochre, brown, orange, red, purple, product range:

magenta, blue, green, lime and black.

thinning: Dilution is not required, ready for use.

consumption: 0.10 | Kemoton Plus / 15 | dispersive paint

preparation and application

Intended for tinting of all types of interior wall paint. The content of one bottle is enough to tint 15 L of dispersive paint in gentle, pastel shades. Before use, shake the bottle well in its material: original packaging and mix the contents well into the paint by hand or with a suitable mixer.

Immediately after finishing the work, wash the tool with water. In case of any questions,

contact the sales and technical advisor of Chromos-Svjetlost.

safety measures: General rules for construction work must be complied with. Keep out of reach of children.

Wear protective equipment. Before use, read the Technical and Safety Sheet of the product.

transport and storage: Store in dry and aired areas away from direct sunlight at temperatures ranging from +5 °C +25

°C. Do not expose the product to direct sunlight, in winter protect from freezing.

shelf life: 1.5 years in unopened packaging.

disposal of leftover product and packaging:

Empty the packaging of its contents completely. Dispose of it at a recycling yard. Legal persons must deliver the packaging as packaging waste to a licenced waste collector.

quality control:

Product quality characteristics are determined by internal production specifications as well as European and Croatian standards. The product is under constant supervision of the factory

quality control of Chromos-Svjetlost d.o.o.

other information:

Mechanical damage on dark colours causes the appearance of light stripes. This phenomenon is specific to dark colours and does not affect the quality of the coating.

general remarks:

Technical values apply only to base products. Tinting paint can result in minor deviations from individual technical characteristics. Depending on the properties of the substrate and the method of application, minor deviations in colour compared to the colour chart are possible. The colour of the product must be checked on a small test surface before application, as we will not be able to accept any complaints later. Before using the product, the customer must check the colour of the product, and upon noticing any incompatibility, the customer must stop the application of the product and contact the manufacturer, otherwise a complaint will not be accepted. The technical data are the result of our technical knowledge and experience, and are provided with the intention of achieving optimal results when working with Chromos-Svjetlost products. The data do not contain any legal or secondary obligation on the part of the manufacturer nor do they release the customer from the obligation to verify the suitability of the product for a specific purpose. Due to the use of natural raw materials in our products, minor deviations from certain values are possible during individual deliveries. When applying the product on substrates that are not specified in corresponding documentation, consult the manufacturer. The manufacturer reserves the right to make further changes to the technical data sheet. Only the latest version is valid. Updated technical data sheets are available at www.chromos-svjetlost.hr or can be requested from the manufacturer via the contact e-mail listed below. For more detailed information, please contact our technical service. Before use, read the safety labels on the product packaging, while the Technical and Safety Sheets are available on request.



Quality and environmental protection management system certified by TUV Croatia; August, 2021 Certificate numbers: 44 100 134668 / 44 104 134668