

PRODUCT TYPE	AQUALUX LAZUR BASE is a wood base coat intended for protection of all types of wooden constructions exposed to weather. Contains a biocidal substance which protects the surface from fungus, mould and algae. Contains < 0.3 % active substance – IPBC. Used on constructions exposed to weather, prior to application of AQUALUX WOODSTAIN.
PRODUCT RANGE	AQUALUX LAZUR BASE
COVERAGE	8-13 m ² /l
VISCOSITY	10–11 s (4 mm, 20 °C) according to HRN EN ISO 2431:2012
DENSITY	1,01 -1,02 kg/l (HRN EN ISO 2811-1:2016)
EU VOC CONTENT	EU VOC: A(f), 130 g/l; max. 3 g/l
AREA OF APPLICATION	AQUALUX LAZUR BASE is suitable for all types of wood. Required as a bio-protective base coat before application of AQUALUX WOODSTAIN on wooden constructions exposed to strong weather (windows, railings, etc).
METHOD OF APPLICATION	Apply onto dry and well-prepared wooden surfaces (maximum 12% moisture content) by dipping, spraying, roller or brush on all sides of protected wood, as long as the wood absorbs the product. In case of subsequent woodwork surfaces should be treated again. AQUALUX WOODSTAIN can be applied after 2-3 hours of drying. Product can be used for interior surfaces in living spaces with good ventilation!
STORAGE	Store in a dry and well-ventilated place out of direct sunlight at a temperature between +5°C and 25 °C.
SHELF LIFE	2 years
NOTE	Product is non-flammable! KEEP FROM FREEZING!

The manufacturer reserves the right to make subsequent changes. For additional information, contact our technical support! The technical data contained herein is given with the intention of achieving optimal results when working with CHROMOS-SVJETLOST products without any obligation on the manufacturer's part.



Za nijansu bolji!